

Part No. 607049



The AC-H-End terminating-plug set, consisting of the AC-HR-End and AC-HT-End terminating plugs, is used as an alignment and setup aid for SOLID-4E host models.

The AC-HR-End terminating plug is used for receiver host models.

The AC-HT-End terminating plug is used for transmitter host models.

Safety notices

! WARNING

Risk of injury due to insufficient safety distance

The integration of a guest device results in a longer reaction time. For this reason, a larger safety distance must be calculated.

↳ Observe the relevant information on calculating the safety distance provided in the Connecting and Operating Instructions.

! WARNING

Improper use may result in loss of the protective function

The terminating plugs are not intended for continuous operation and protective mode.

↳ Use the terminating plugs only as an alignment and setup aid.

! WARNING

Risk of injury due to missing rear area protection

↳ When using the terminating plug, use appropriate means to ensure that it is not possible to step behind the safety light curtain.

! WARNING

Risk of injury due to unpredictable machine behaviour

Any change to the protective device may result in unpredictable machine behaviour.

↳ Following any change, have the protective device tested by a competent person.

Please also observe the Connecting and Operating Instructions for the SOLID-4E. Download from <http://www.leuze.de/solid>.

Ordering information

Part No.	Article	Description
426122	AC-H-End – terminating plug	Terminating plug – set consisting of AC-HT-End and AC-HR-End for SOLID-4E host models

We reserve the right to make changes