

Part No. 607412



The AC-H-End terminating-plug set, consisting of the AC-HR-End and AC-HT-End terminating plugs, is used as an alignment and setup aid for SOLID-4E host models.

The AC-HR-End terminating plug is used for receiver host models.

The AC-HT-End terminating plug is used for transmitter host models.

Safety notices

!WARNING

Risk of injury due to insufficient safety distance

The integration of a guest device results in a longer reaction time. For this reason, a larger safety distance must be calculated.

↳ Observe the relevant information on calculating the safety distance provided in the Connecting and Operating Instructions.

!WARNING

Improper use may result in loss of the protective function

The terminating plugs are not intended for continuous operation and protective mode.

↳ Use the terminating plugs only as an alignment and setup aid.

!WARNING

Risk of injury due to missing rear area protection

↳ When using the terminating plug, use appropriate means to ensure that it is not possible to step behind the safety light curtain.

!WARNING

Risk of injury due to unpredictable machine behaviour

Any change to the protective device may result in unpredictable machine behaviour.

↳ Following any change, have the protective device tested by a competent person.

Please also observe the Connecting and Operating Instructions for the SOLID-4E. Download from <http://www.leuze.de/solid>.

Ordering information

Part No.	Article	Description
426122	AC-H-End – terminating plug	Terminating plug – set consisting of AC-HT-End and AC-HR-End for SOLID-4E host models

We reserve the right to make changes